

Split type wall mounted air conditioner

Technical data

SET MODEL

Power consumption

ADI/ADO-26HPR1

230/1/50

V/ph/Hz

Cooling mode Heating mode

Capacity		3000	2600	W
Power input		840	820	W
Rated current		4,8	4,6	A
Eficiency (EER/COP)		3,7	3,6	
Refrigerant		R410a (900 g)		
INDOOR UNIT MODEL		ADI-26HPR1		
Ventilator air flow	Hi/Med/Low	550/410/300		m ³ /h
Sound Pressure (Lp)	Hi/Med/Low	38/35/32		dB(A)
Sound Power (Lw)	Hi/Med/Low	47/44/41		dB(A)
Net dimensions	LxHxD	795x270x165		mm
Packing dimensions	LxHxD	850x335x285		mm
Weight	brutto/neto	12.5/10		kg
OUTDOOR UNIT MODEL		ADO-26HPR1		
Sound Power (Lw) / Pressure (Lp)		63/54		dB(A)
Compressor type		rotary		
Compressor model		PA108X1C-4FTDE (Toshiba)		
Fan type		Axial 1-fan		
Fan motor power		56		W
Net dimensions	LxHxD	780x540x250		mm
Packing dimensions	LxHxD	910x575x335		mm
Connection holes dimensions	L1xD1	549x250		mm
Weight	brutto/neto	34/31		kg
Pipe connections	liquid/gas	1/4 - 3/8		inch
	indoor condensate	16		mm
Electrical connections	indoor&outdoor	5 x 2.5		mm ²
	power to indoor	3 x 2.5		mm ²

Hind paigalduseta 450€



Split type wall mounted air conditioner

Technical data

SET MODEL		ADI/ADO-35HPR1		
Power consumption		230/1/50		V/ph/Hz
		Cooling mode	Heating mode	
Capacity		3500	3800	W
Power input		1100	1050	W
Rated current		4.8	4.6	A
Eficiency (EER/COP)		3.2	3.6	
Refrigerant		R410a (1050 g)		
INDOOR UNIT MODEL		ADI-35HPR1		
Ventilator air flow	Hi/Med/Low	650/510/400		m ³ /h
Sound Pressure (Lp)	Hi/Med/Low	40/37/34		dB(A)
Sound Power (Lw)	Hi/Med/Low	49/46/43		dB(A)
Net dimensions	LxHxD	845x286x165		mm
Packing dimensions	LxHxD	905x350x285		mm
Weight	brutto/neto	13.5/10.5		kg
OUTDOOR UNIT MODEL		ADO-35HPR1		
Sound Power (Lw) / Pressure (Lp)		64/55		dB(A)
Compressor type		rotary		
Compressor model		PA140X2C-4FT (Toshiba)		
Fan type		Axial 1-fan		
Fan motor power		56		W
Net dimensions	LxHxD	780x540x250		mm
Packing dimensions	LxHxD	910x575x335		mm
Connection holes dimensions	L1xD1	549x250		mm
Weight	brutto/neto	37/34		kg
Pipe connections	liquid/gas	1/4 - 1/2		inch
	indoor condensate	16		mm
Electrical connections	indoor&outdoor	5 x 2.5		mm ²
	power to indoor	3 x 2.5		mm ²

Hind paigalduseta 550€

